

Gladiator

High Speed Trailer Tires

GLADIATOR TRAILER TIRES LIMITED WARRANTY

GLADIATOR ST LIMITED WARRANTY

American Pacific Industries, Inc. (API) hereby warrants that every new Gladiator ST Trailer Tire purchased from API bearing the brand name Gladiator to be free from conditions of workmanship and material that would cause the tire to become unserviceable for the life of the original tread less 2/32". The life of the original usable tread ends when the tire tread has worn down to 2/32" remaining, at which point the tire is considered to be fully worn out. This warranty applies only to the original purchaser for a period of two (2) years from the date of manufacture. API's liability under this warranty shall be limited to replacement and/or credit for the cost of the tire.

GENERAL WARRANTY AND WARRANTY OBLIGATION

If any Gladiator ST tire becomes unserviceable, API will do either of the following:

- A. If the tire becomes unserviceable due to material or workmanship during the first 2/32" of the original tread, API will replace such tire with a comparable new Gladiator tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- B. If the tire becomes unserviceable due to material or workmanship after the first 2/32" of tread wear, a credit will be given toward the purchase of a comparable new tire in proportion to the usable tread remaining. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.

Adjustment for out-of-balance or out-of-round tires is not covered by this warranty.

EXCLUSIONS

- A. All API warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not assignable to subsequent purchasers or vehicles.
- B. This limited warranty is applicable only in the United States, Canada or Mexico and any tire used on a vehicle registered or operated outside of these areas is not covered by this warranty.
- C. The following is not covered by the Limited Warranty:
 1. Tires branded or marked "Non-Adjustable" (N/A) or "Blemished (Blem), or previously adjusted.
 2. Tires that are deemed out-of-round or out-of-balance
 3. Failure, damage or irregular wear due to:
 - a. Road hazards (i.e. puncture, cut, snag, impact breaks, etc.);
 - b. Fire, accident or vandalism;
 - c. Mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d. Misapplication of the tire, use of improper inner tube;
 - e. Alteration of the tire or addition of foreign material or transfer from one vehicle to another;
 4. Cost of service, mounting and dismounting.
 5. Loss of time or use, inconvenience, or any incidental or consequential damages of any type or nature.

OWNER'S OBLIGATIONS

In order to be eligible for Limited Warranty Service, the owner must:

- A. Present the tire to an authorized dealer;
- B. Present proof of purchase to the satisfaction of the dealer;
- C. Complete and sign an API Warranty Claim Form, which is available from any authorized dealer; and
- D. Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of API tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

QUALITY SPEAKS FOR ITSELF • EXPERIENCE THE DIFFERENCE™



800.944.8414



gladiatortires.com



@gladiatortires



/gladiatortires

GLADIATOR ST SEPT 2017

Gladiator

High Speed Trailer Tires



QR35



QR25



QR15

EC SAFE

ENGINEERED TO PERFECTION®

Gladiator

High Speed Trailer Tires

- Steel belted construction for added strength and stability
- Advanced tread compound designed to improve fuel economy and resist weather cracking
- Designed with stone ejectors between the tread area to protect casing and prevent stone drilling



Tire Size	Ply	Load Index SINGLE/DUAL	Speed Symbol	Overall Diameter INCHES	Section Width INCHES	Tread Depth 32ND'S	Load Capacity SINGLE/DUAL (LBS)
QR35-TR ALL-STEEL							
ST235/85R16*	14	132/127	N	31.7	9.3	13	4400/3860



Tire Size	Ply	Load Index SINGLE/DUAL	Speed Symbol	Overall Diameter INCHES	Section Width INCHES	Tread Depth 32ND'S	Load Capacity SINGLE/DUAL (LBS)
QR25-TS							
ST175/80R13	6	91/87	N	24.0	7.0	9	1360/1200
ST205/75R14	6	100/96	N	26.1	8.0	9	1760/1570
ST205/75R14	8	105/101	N	26.1	8.0	9	2040/1820
ST215/75R14	6	102/98	N	26.7	8.5	9	1870/1650
ST205/75R15	6	101/97	N	27.1	8.0	9	1760/1570
ST205/75R15	8	107/102	N	27.1	8.0	9	2150/1870
ST225/75R15	8	113/108	N	28.3	8.8	9	2540/2200
ST225/75R15*	10	117/112	N	28.3	8.8	9	2830/2470
ST225/90R16*	14	122/118	N	31.8	8.7	12	3300/2910
ST235/80R16*	10	124/120	N	31.2	8.9	12	3520/3080
ST235/80R16*	12	125/121	N	31.2	8.9	12	3640/3200
ST235/85R16*	12	128/124	N	31.7	9.0	12	3960/3520
ST235/85R16*	14	132/127	N	31.7	9.0	12	4400/3860
ST255/85R16*	12	130/126	N	33.1	10.0	10	4190/3750

* Tread NOT shown

* REQUIRES SPECIAL HIGH LOAD CAPACITY WHEELS AND HIGH PRESSURE TIRE VALVE.



Tire Size	Ply	Load Index SINGLE/DUAL	Speed Symbol	Overall Diameter INCHES	Section Width INCHES	Tread Depth 32ND'S	Load Capacity SINGLE/DUAL (LBS)
QR15-STB							
ST175/80D13	6	91/87	J	24.0	7.0	8	1360/1195
ST205/75D14	6	100/96	J	26.2	8.0	8	1760/1550
ST205/75D15	6	101/97	J	27.1	8.0	8	1820/1602
ST205/90D15**	10	114/109	J	29.6	8.0	13	2335/2040
ST225/75D15	8	113/108	J	28.3	8.8	13	2540/2200
ST225/90D16**	10	115/110	J	31.8	8.5	13	2755/2470
ST225/90D16**	12	121/117	J	31.8	8.5	13	2910/2605
ST235/80D16*	10	123/119	J	30.8	9.3	13	3420/3000
8-14.5*	14	120	J	27.8	8.0	8	3100

QUALITY SPEAKS FOR ITSELF®
EXPERIENCE THE DIFFERENCE®

ECO SAFE

